

# MOLYDUVAL

## Sekorex CHA 40 ZLM



### Synthetic Chain Lubricant with Solid Lubricants

A very adhesive chain grease spray for high loaded chains. Because of its good water resistance and oxidation stability it is even useful under corrosive or wet conditions. Free of mineral oil. The contained synthetic ester fluids offer good creeping properties and good temperature stability. Beyond the maximum temperature there will be emergency lubrication by the white solid lubricants. The product contains solvent for easier application.

#### Properties

- \* very high pressure ability
- \* high temperature resistance
- \* strong tackiness
- \* good lubrication performance
- \* PTFE solid lubricant share offering additional friction reducing
- \* good penetrative properties
- \* low residue forming

#### Applications

- \* for chains in high temperature sectors
- \* for chains, drive and transport chains, in conveying machines, pasteurize plants, sorting stations, peelers, packing and labelling machines, shrinking tunnels
- \* for chains in textile industry
- \* for wire rope lubrication at cranes or containers
- \* for motorcycle chains

#### Technical Datas

Color		white
Base Fluid		PAO, Ester
Temperature Range	°C	-30 -> +250
Temperature Range Trockenschmierung	°C	1000
Density 15°C	kg/m³	850
Particle Size Ø	µm	0,35

*The indicated service temperatures are guide values depending on the lubricants composition and on the application. They may vary in case of special influences or ongoing use.*

For further information, please see our website [www.molyduval.com](http://www.molyduval.com) or consult your local representative.

The technical data in this information sheet represents our present knowledge and is based on our general experience. It is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary tests with the selected product to ensure that the product is safe, effective and fully satisfactory for the intended end use. It does also not form part of any sales contract as guaranteed properties of the delivered material.